

Guillotine Shears KMT S 1353



SKU: 133610

The KMT S series has stable construction and is of high quality. The modern guillotine shears have a powerful, motorised drive that enables high cutting performance. The construction with guided cutting blades and a small cutting angle enables cuts with little twist in the workpiece. The backgauge can be precisely positioned using the handwheel accessible from the front.

- Solid steel weldment
- Blades with multiple cutting surfaces
- Back gauge can be positioned from the front of the machine
- Work area is secured by light curtain

TECHNICAL SPECS

WORKING AREA

1350 mm
2.32 deg
840 mm
390 mm
2 positions
940 mm
34 H/min

BACK GAUGE

CUTTING CAPACITIES

Plate thickness (max.) - 450 N/mm²	0.1 mm - 3 mm
Plate thickness(max.) - 700 N/mm²	1.5 mm

DRIVE CAPACITY

Motor rating main drive 3 kW

MEASURES AND WEIGHTS

Overall dimensions (length x width x height)	1.93 m x 2.15 m x 1.31 m
Weight	1250 kg











PRODUCT DETAILS

Machine Frame and Drive System

- The machine frame is made of a very rigid, solid steel weldment
- The upper knives are reversible for use of both sides, and the lower knives feature 4 cutting edges
- A rigid, continuous hold-down fixes the sheet metal plate right in front of the cut line

Material Support

- The rigid side angle stop simplifies alignment of the plate to the cut line
- Rugged support arms ensure a strong hold of large plates
- Material support rollers are recessed in the table for easy workpiece handling

Ergonomic Design

- The mobile foot switch gives the operator added flexibility and both hands are free for handling the workpiece
- For a better view of the cut line, the hand safety guard can be flipped up or down
- The bright LED illumination of the cut line creates a clearly visible shadow on the marked line

Rear stop:

- The back gauge can be positioned precisely via a hand-wheel
- The easy accessible work area at the back gauge is secured by light curtain
- The machine can be equipped with an optional NC-controlled back gauge for a length up to 1000 mm, or a sheet hold-up device

STANDARD EQUIPMENT

Foot pedal with emergency stop switch Cut-line lighting Squaring arm Support arms with T-slots and tilting stop Manual 750 mm backgauge Ball bearing front table Light curtain Top blade with 2 sides Finger guard Operator instructions

OPTIONAL EQUIPMENT

extra blade set for KMT S 1353 - 133610, SKU : 253803



KNUTH on YouTubeInformation to the point

On our YouTube channel you can find videos for nearly all machines from our program. We show the machines from current deliveries and you get an impression of the handling, the processing quality and the machining performance.

Are you interested in a machine for which you cannot find a current video? Please feel free to contact us!