



SKU : 162340

The TSB bench drill series impresses with its compact dimensions and high drilling performance for a wide range of applications. They are suitable for every workshop, from steel construction to repair shops. The machines have a main spindle gearbox for high torque and a particularly wide speed range. A swiveling drill head enables drilling at an angle. The TSB 35 also has an automatic quill feed for large drilling diameters.

- Compact table design
- Swiveling drill head
- Manual transmission for high torque



TECHNICAL SPECS

WORKING AREA

Drilling capacity	25 mm
Tapping capacity, steel	M 16
Foot set up area (length x width)	310 mm
Vertical head travel	470 mm
Spindle nose-to-foot distance	650 mm
Throat	240 mm
Column diameter	95 mm

HEADSTOCK

Spindle speed	125 1/min - 2825 1/min
Spindle mount	3 MT
Quill stroke	110 mm

FEED

Quill feeds	- mm/R
-------------	--------

DRIVE CAPACITY

Motor rating main drive	0.75 kW
-------------------------	---------

MEASURES AND WEIGHTS

Overall dimensions (length x width x height)	0.7 m x 0.41 m x 1.56 m
Weight	220 kg



PRODUCT DETAILS

High Power at a Low Price

- Drilling capacity 25 mm
- Throat 240 mm
- Spindle nose-to-foot distance 650 mm
- Spindle speed (6) 125-2825 rpm
- Spindle mount MT 3
- Rigid cast-iron construction
- Height-adjustable machine head
- 6 speed steps
- Rectangular table with T-slots and circumferential coolant groove

STANDARD EQUIPMENT

Base
Protective shield
LED work lamp
Drill chuck
Operating tools
Operator instructions



KNUTH on YouTube Information to the point

On our YouTube channel you can find videos for nearly all machines from our program. We show the machines from current deliveries and you get an impression of the handling, the processing quality and the machining performance.

**Are you interested in a machine for which you cannot find a current video?
Please feel free to contact us!**