



SKU : 131508

The HPK A series is a series of hydraulic presses with a C-shaped design for deep drawing, forming, and notching processes. These machines are manufactured in Europe, and all components and parts meet extremely strict quality requirements. The possible force ranges from 40 to 300 tons. The entire series has large ram plates on the cylinder and work table with clamping flutes for mounting tools and accessories. Mobile 2-hand operation guarantees safety, and the travel distance is defined with adjustable limit switches. We also offer customized solutions that are based on individual customer requirements.

- Classic design with c-frame
- Completely built in Europe for high reliability
- Designed for testing or batch production
- Possibility of Industry 4.0 integration
- Customized solution available

TECHNICAL SPECS

WORKING AREA

Pressure force	70 t
Table dimensions	700 mm x 500 mm
Stroke	500 mm
Ram-plate size	700 mm x 350 mm
Throat depth	250 mm
Stroke speed	5 mm/s

RAPID FEED

Rapid feed	24 mm/s
------------	---------

DRIVE CAPACITY

Motor rating	4 kW
--------------	------

MEASURES AND WEIGHTS

Overall dimensions (length x width x height)	1.5 m x 1 m x 2.5 m
Weight	2100 kg



Space saving hydraulic system located accessibly inside the frame



Two circular guides ensure maximum ram plate parallelism during stroke movement



Diagonally aligned slots for easy centered tool clamping

PRODUCT DETAILS

- Made in Europe - perfectly welded C-frame steel construction for high rigidity, designed for maximum machine force
- Large ram plates and work tables to ensure large tools or multiple setups
- Hydraulic presses are extremely versatile due to their distance/time flexibility of the stroke
- A powerful hydraulic cylinder and two self-lubricating circular guides ensure precise and uniform feed of the ram plate during press operations
- Precision-machined cylinder surfaces and high-quality seals ensure low wear and long lasting reliability
- Rapid adjustment of stroke length via easy to set stops
- Space saving hydraulic system located accessibly inside the frame
- 2-step hydraulic pump for fast rapid feeds and optimum stroke speeds
- Ram plate and work table with t-slots for tool clamping
- A mobile control panel provides flexibility, while additional controls are easily accessible integrated in the control cabinet
- All components are made according to strict standards, and the entire construction meets European safety guidelines

STANDARD EQUIPMENT

Two-hand control panel
Adjustable stops for up/downstroke
Pressure gauge
Movable upper table with 2 guides and T-slots
Automatic operation
Automatic cylinder return
Siemens PLC
Hydraulic unit with 2 speed automatic change
Pressure switch
Timer
Operator manual

OPTIONAL EQUIPMENT

- Light curtain L = 1,000 mm, SKU : 253855
- upgrade to Siemens KTP 700 Basic digital control, SKU : 253856
- upgrade from 2 to 4 lateral slides, SKU : 253857
- pieces counter, SKU : 253860
- Air/oil heat exchanger with decompression valve, SKU : 253861
- decompression valve, SKU : 253862



KNUTH on YouTube Information to the point

On our YouTube channel you can find videos for nearly all machines from our program. We show the machines from current deliveries and you get an impression of the handling, the processing quality and the machining performance.

**Are you interested in a machine for which you cannot find a current video?
Please feel free to contact us!**