

Conventional Vertical Lathes

VDM 2600 S



SKU : 301396

The VDM series of vertical lathes offers modern, conventional solutions for machining large workpiece diameters and heavy workpiece weights. Their design enables particularly easy and safe loading and unloading. The feed drive is a high-torque servo motor and a powerful hydraulic system clamps the crossbeam. The main drive provides high torque for heavy machining and a side support is available for machining the outer contour. The standard mounted 3-axis position indicator ensures precision.

- Optimum assembly with crane and forklift
- Infinitely variable feed control via servo motor
- Long, sturdy vertical boom
- Side support with boom and independent feed
- Reduction gear drive for high torque

TECHNICAL SPECS

WORKING AREA

Rotating diameter (max.)	2600 mm
Turning diameter of upper tool holder	2600 mm
Turning diameter of side tool holder	2300 mm
Machining height (max.)	1500 mm
Swivel range of upper tool holder	± 30°
Workpiece length (max.)	1500 mm
Workpiece weight (max.)	10000 kg

TRAVELS

Travel X1 axis, upper support	1300 mm
Travel Z1 axis, upper support	1000 mm
Travel W-axis, traverse	1100 mm
Travel X2 axis, side support	730 mm
Travel Z2 axis, side support	1180 mm

HEADSTOCK

Speed range	1.4 1/min - 45 1/min
Spindle torque (max.)	32000 Nm
Rotary table diameter	2300 mm

RAPID FEED

Rapid feed of upper support	1800 mm/min
Rapid feed of side support	1800 mm/min

FEED

Feed speed X-axis	0.8 mm/min - 86 mm/min
Feed speed Z-axis	0.8 mm/min - 86 mm/min
Feed speed W-axis	440 mm/min

TOOLING


Tool holder	30 mm x 40 mm
Tool weight max.	50 kg

DRIVE CAPACITY

Motor rating main drive	37 kW
Motor rating X-axis	4.7 kW
Motor rating Z-axis	4.7 kW

MEASURES AND WEIGHTS

Overall dimensions (length x width x height)	7.9 m x 5.3 m x 5.4 m
Weight	27500 kg



PRODUCT DETAILS

- Infinitely variable feed control via servo-motor
- Optimum tooling and easy access for cranes and forklift trucks
- Heavy-duty column with wide, hardened guideways
- Hydraulic clamping of cross traverse
- Rigid guide construction ensures maximum rigidity and accuracy of the vertical boom
- Spindle runs in a high-precision two-row roller bearing and is adjustable
- Reduction gear drive ensures high torque and a speed range of 10 - 315 rpm
- Servo motor technology ensures powerful, infinitely variable feed of the vertical boom



Vertical support includes a 5-station tool holder, side support with independent feed for inside and outside turning

STANDARD EQUIPMENT

- 3-axis position indicator X.Pos 3.2
- Totally enclosed work space
- Chip conveyor
- Tool holder vertical
- Tool holder horizontal
- Automatic central lubrication
- Work lamp
- Anchor bolts
- Operating tools
- Operator manual

OPTIONAL EQUIPMENT

- Coolant System, SKU : 251430



KNUTH on YouTube Information to the point

On our YouTube channel you can find videos for nearly all machines from our program. We show the machines from current deliveries and you get an impression of the handling, the processing quality and the machining performance.

**Are you interested in a machine for which you cannot find a current video?
Please feel free to contact us!**